OSRAM

BATTERYcharge 7PIN | 3PHASE | 32 AMP

Charging Cable for electric and plug-in hybrid vehicles



Type 2 to Type 2

Charge at home and on the moveType 2 to Type 27PIN | 3PHASE



32 Ampere

Connects to any charging unit or station with a 32A (3 Phase) type 2 connection



22 kWh

Charge your 60kW battery in ca. 3 hours



5m cable length

Ergonomic handles for optimal handling and a cable length of 5 meters



Drive with OSRAM into a more emission-free future

Discover the world of electric driving with OSRAM. Charge your all-electric or plug-in hybrid vehicle from type 2 at any compatible charging station equipped with a 32A (3-phase) type 2 connection. The charging cable is equipped with ergonomic handles for optimal handling and has a cable length of 5 meters. It is suitable for use at public charging stations and at home. In addition, the charging cables are equipped with dust protection caps and tested for water resistance according to IP65 and shock resistance according to IK10. Even when connected, the electrical contact points are protected against the ingress of dust and splash water in accordance with IP65 and IK10. The scope of delivery also includes a durable, compact storage bag to neatly store the cable after charging. In addition, the product is TÜV and CE certified and comes with a 2-year guarantee*

Product datasheet

Technical data


Product information


Order reference	OCC23P05
Storage Case	Yes
Number Of Phases	3
Vehicle Charger Type	Type2
Charging Point Charger Type	Type2

Electrical data

Nominal wattage	22000 W
Nominal voltage	480 V
Nominal current	32 A

Dimensions & weight





Length	5000 mm
Width	70.0 mm
Height	120.0 mm

Lifespan

Guarantee	2 years
-----------	---------

Additional product data

Operating Temperature -40 +80 °C

Certificates & standards

Standards	TÜV/CE
Type of protection	IP65
IK Class	IK10

Product datasheet

Country specific categorizations

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration	07-04-2022		
Primary Article Identifier	4052899624139		
Declaration No. in SCIP database In work			

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899624139	BATTERY charge 7PIN 3PHASE 32 AMP	Sleeves 1	340 mm x 200 mm x 108 mm	7.34 dm³	3940.00 g
4052899624207	BATTERY charge 7PIN 3PHASE 32 AMP	Shipping carton box 4	496 mm x 406 mm x 387 mm	77.93 dm³	16710.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction

*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

